

# IPVC Grit Hose

## Abrasion resistant hose



### Application:

Suction and discharge for sand, grains, gravel, cement and iron. Commonly used in concrete pumping, shipyards and ships; and transfer of powdered and granular materials.

### Features:

- Highly abrasion-proof
- Pressure resistance
- Very robust
- Flame retardant to UL94- HB



### Material:

Wall: Soft compound abrasion PVC and rubber  
Helix: Rigid PVC



### Working Temperature:

-10deg C to +60deg C

ID (mm)	OD (mm)	Overpressure (bar)	Stock Lengths (m)	Order No.
38	52	7000	20	2-5-038-000
51	68	6000	20	2-5-051-000
63	80	6000	20	2-5-063-000
90	98	6000	20	2-5-076-000
102	130	5000	20	2-5-102-000
127	158	4000	15	2-5-127-000
152	183	3000	15	2-5-152-000

ID	OD	Length (m/roll)	Working Pressure (bar)	Weight (g/m)
38	52	20	7	370
63	68	5	0.15	480
76	87	5	0.13	550
90	96	5	0.1	590
102	108	5	0.1	650
127	133	5	0.09	800
152	159	5	0.08	990
203	210	5	0.05	1300
254	262	5	0.03	1600
305	314	5	0.02	1900

